



68	Seal Ring	02	PA66-GF	Nylon
12	Loose Rib	01	GCr15-GB/T18254	
04	Needle Roller(Ø2.75x 14.8)	24	GCr15-GB/T18254	
02	Shaft	01	20CrMo-GB/T3077	
01	Outer Ring	01	GCr15-GB/T18254	
No.	Name	Qty	Material	Attention

Notes: 1. Rated Load: Cr= 20.5 KN Cor= 28.9 KN 2. Radial internal clearance: 0.020-0.045mm 3. Bearing surface Black oxidation 4. Grease: shell Grease 5. Shape location Tolerance should be to current standard.					Units are in Inches ASME Y14.5 X.X ± 0.040 X.XX ± 0.015 X.XXX ± 0.005 X.XXXX ± 0.0005		 Third Angle Projection		State: Approval Pending		QTY:		Scale: 1:1									
Passing on and copying of this document, use and its contents is not permitted unless expressly permitted. Violators are liable for damages. All rights for the case of patent award or utility model registration. (DIN34/ISO16016)					Date		Name		Hardness: - HRC		Material: -											
									Name / Title: STUD TYPE TRACK ROLLER BEARING		Finish: -											
Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich erlaubt. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten. (DIN34/ISO16016)					Check		Aprv		Mat'l Dims: CCF 1-1/2 S		Description: -											
									Machine Name: -		Machine No: -											
					Department				Tool Name: -		Tool No: -											
									Drawing Number: 0009200800		Sheet Size ANSI A 1 of 1											
									SAP Part Number: -		Replacement for: -											
									Rev		ECN		Description		Date		Name		Made From: -		Replaced by: -	