



5	Shaft	1	20CrMo	58-62 HRC	
4	Retaining Washer	1	GCr15	50-55 HRC	
3	Seal	2	PA66		
2	Roller	44	GCr15	61-65 HRC	Ø 3.173 x 31.6
1	Outer ring	1	20CrMo	58-62 HRC	
Number	Item	Quantity	Material	Heat	Remark

Notes: 1. Bearing must be clean, free of burrs, scratches and other foreign matters 2. Radial internal clearance 0.02-0.045 mm 3. Dynamic load: 15720 LBS, static load: 24910 LBS 4. Bearing pre lubricated with EP-2 extreme pressure grease 5. Black oxide on external surfaces Passing on and copying of this document, use and its contents is not permitted unless expressly permitted. Violators are liable for damages. All rights for the Case of patent award or utility model registration. (DIN34/ISO16016) Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich erlaubt. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten. (DIN34/ISO16016)					Units are in Inches ASME Y14.5 X.X ± 0.040 X.XX ± 0.015 X.XXX ± 0.005 X.XXXX ± 0.0005		 Third Angle Projection		State: Approval Pending		QTY:		Scale: 1:1	
					Date		Name		Hardness:		- HRC			
					Drawn		SD		Name / Title:		CAM FOLLOWER			
					Check		-		Mat'l Dims:		CCF-3-SB			
					Aprv		-		Description:		-			
					Department				Machine Name: -		Machine No: -			
									Tool Name: -		Tool No: -			
									Drawing Number:		0009202500			
									SAP Part Number:		-			
									Replacement for: -		Replaced by: -			
											Sheet Size ANSI A 1 of 1			
Rev	ECN	Description	Date	Name	Made From: -									