



5	Shaft	1	58-62 HRC
4	Retaining washer	1	50-55 HRC
3	Seal	2	
2	Roller	38	61-65 HRC
1	Outer Ring	1	58-62 HRC
NUMBER	ITEM	QUANTITY	HEAT

Notes:  
 1. Bearing must be clean, free of burrs, scratches and other foreign matters  
 2. Radial internal clearance: 0.020-0.045mm  
 3. Dynamic load: 29985 LBS Static load: 44770 LBS  
 4. Bearing pre lubricated with EP-2 Extreme pressure grease  
 5. Black oxide on external surfaces

Passing on and copying of this document, use and its contents is not permitted unless expressly permitted. Violators are liable for damages. All rights for the Case of patent award or utility model registration. (DIN34/ISO16016)

Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich erlaubt. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten. (DIN34/ISO16016)

Units are in Inches  
 ASME Y14.5  
 X.X ± 0.040  
 X.XX ± 0.015  
 X.XXX ± 0.005  
 X.XXXX ± 0.0005

 Third Angle Projection	State: Approval Pending		QTY:	Scale: 1:2
	Material: -		Finish: -	
Date		Name		Hardness: - HRC
Drawn	2016/11/14	SD		Name / Title: CAM FOLLOWER
Check	-	-		Mat'l Dims: CCF-4-SB
Aprv	-	-		Description: -
Department		Machine Name: -		Machine No: -
-		Tool Name: -		Tool No: -
-		Drawing Number: 0009203200		Sheet Size ANSI A 1 of 1
+		SAP Part Number: -		
Rev		ECN	Description	Date
-		-		Name
-		-		Made From: -
+		Initial Release		Replacement for: -
-		-		Replaced by: -

