



SECTION A-A

NO.	NAME	QTY
68	SEAL RING	2
12	LOOSE RIB	1
04	NEEDLE ROLLER (P2.75X14.8)	24
02	SHAFT	1
01	OUTER RING	1

Notes: 1. Rated Load: Cr=20.5 KN, Cor=28.9 KN 2. Radial internal clearance:0.020-0.045mm 3. Bearing surface Black oxidation 4. Grease:shell Grease 5. Shape location Tolerance should be to current standard.					Units are in Inches ASME Y14.5 X.X ± 0.040 X.XX ± 0.015 X.XXX ± 0.005 X.XXXX ± 0.0005		Third Angle Projection		State: Approval Pending QTY: Scale: 2:1	
Passing on and copying of this document, use and its contents is not permitted unless expressly permitted. Violators are liable for damages. All rights for the Case of patent award or utility model registration. (DIN34/ISO16016)					Date 2016/11/21		Name AS		Hardness: - HRC	
Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich erlaubt. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten. (DIN34/ISO16016)					Drawn -		Check -		Name / Title: STUD TYPE TRACK ROLLER BEARING	
					Department LoadRunner		Machine Name: - Machine No: -		Mat'l Dims: CFH 1-1/2 S	
					Rev ECN Description Date Name		Machine No: - Tool No: -		Description: HD w/Seals	
					Made From:-		Drawing Number: 0009216100		Sheet Size ANSI B 1 of 1	
					Replacement for:-		Replaced by:-			

