



NO.	NAME	Q'TY
68	SEAL RING	2
12	LOOSE RIB	1
04	NEEDLE ROLLER	24
02	INNER RING	1
01	OUTER RING	1

Notes: 1. Rated load: Cr =20.5 KN, Cor=28.9 KN ; 2. Radial internal clearance: 0.020-0.045mm ; 3. Bearing surface blackening treatment: 4. Grease: Shell Grease ; 5. Shape location tolerance should be to current standard.					Units are in Inches ASME Y14.5 X.X ± 0.040 X.XX ± 0.015 X.XXX ± 0.005 X.XXXX ± 0.0005		 Third Angle Projection		State: Approval Pending QTY: - Scale: 3:1	
Passing on and copying of this document, use and its contents is not permitted unless expressly permitted. Violators are liable for damages. All rights for the Case of patent award or utility model registration. (DIN34/ISO16016)					Date: 2016/10/18 Name: AS		Hardness: - HRC		Name / Title: YOKE TYPE TRACK ROLLER BEARING	
Weitergabe sowie Vervielfältigung dieser Unterlage, Verwertung und Mitteilung ihres Inhalts nicht gestattet, soweit nicht ausdrücklich erlaubt. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patenterteilung oder Gebrauchsmuster-Eintragung vorbehalten. (DIN34/ISO16016)					Check: - Aprv: -		Mat'l Dims: CYR 1-1/2 S		Description: SEALED	
Department: LoadRunner					Machine Name: - Machine No: -		Tool Name: - Tool No: -		Sheet Size: ANSI B 1 of 1	
					Drawing Number: 0009220300		SAP Part Number: -		Replacement for: - Replaced by: -	
Rev	ECN	Description	Date	Name	Made From:-					